

# (12) UK Patent Application (19) GB (11) 2 301 297 (13) A

(43) Date of Printing by UK Office 04.12.1996

(21) Application No 9617454.5

(22) Date of Filing 17.02.1995

(30) Priority Data

(31) 940576 (32) 21.02.1994 (33) NO

(86) International Application Data  
PCT/NO95/00037 En 17.02.1995

(87) International Publication Data  
WO95/22400 En 24.08.1995

(71) Applicant(s)

Bjorn Dybdahl  
Lillesund Terrasse 4D, N-5500 Haugesund, Norway

(72) Inventor(s)

Bjorn Dybdahl

(74) Agent and/or Address for Service

Stephenson Harwood  
One, St. Paul's Churchyard, LONDON, EC4M 8SH,  
United Kingdom

(51) INT CL<sup>6</sup>  
B01F 5/06


(52) UK CL (Edition O )  
B1C CAU C122 C2011 C305 C351 C628

(56) Documents Cited by ISA  
GB 2041035 A NO 000174015 B

(58) Field of Search by ISA  
INT CL<sup>6</sup> B01F, F16K  
SE, DK, FI, NO classes as above

(54) A device for the positioning of a throttle/mixing body

(57) The invention relates to a throttling/mixing device for mixing a fluid, especially a two- or multi-phase fluid, flowing in a pipe (1), a pipeline, a container, a tank, a separator, a heat exchanger, e.g. a discharge pipe from said separator etc., particularly, but not exclusively, in connection with fluid sampling, wherein said pipe (1) etc. comprises a valve housing (4) extending laterally of the axis of the pipe (1) etc. and projecting beyond the same at two diametrically opposite sides, and wherein the throttling/mixing device has partly a through-going passage (7), the clear width area of which corresponding to said pipe's (1) etc. fluid flow area and which can be brought to register with said fluid flow area; partly, preferably mutually sloping, but extending in the same main direction throttling channels (8) which, likewise, can be brought to register with said fluid flow area, in order to throttle/mix the fluid. In order to provide a throttling/mixing device wherein the valve housing (4) has a small extent laterally of said pipe (1) etc., maintaining a simple manoeuvring and stable mounting of the valve body (5), the throttling/mixing device has the form of a plug valve, the valve plug (5) thereof being formed with throttling channels (8) crossing the through-going passage (7) substantially right-angled to the passage's (7) longitudinal axis (1'), and that the valve plug (5) is rotatably mounted in the valve housing (4) about the common longitudinal axis thereof.



GB 2 301 297 A